



THREE STAGE VEHICLE WASH WATER INTERCEPTOR TANK

- ~ Reduces pollution
- ~ Reduces effluent charges
- ~ Prevents drain blockages
- ~ Free oil removed
- ~ Packaged one piece system including covers for fast, labour saving installation
- ~ Connection of below ground pipework to connections provided, at time of installation, enabling a water recycle system to be fitted at a later date allowing the user to reduce water and effluent costs, or to continue to use the vehicle wash in the event of any water rationing
- ~ Recommended by all leading vehicle wash manufacturers

SERIES CT



Kirton CT system has been specifically designed for vehicle wash effluents and is extensively used throughout the transport industry.

Type	Overall Size	Weight		Water Capacity			Recommended Use
		Empty	Full	Working	Reserve	Maximum	
CT844	2440 x 1120 x 1370 8'7" x 4'2" x 4'6"	440kg	3730kg	450g 2025L	350g 1575L	800g 3600L	To handle one commercial washer or up to 2 car washes
CT1644	5277 x 1270 x 1370 16'7" x 4'2" x 4'6"	880kg	7460kg	900g 4050L	700g 3150L	1600g 7200L	To handle effluents from 2-4 vehicles washers

Interceptor available in hot dipped galvanised finish or special epoxy paint.

Also available:

- Kirton OS range of titled plate oil interceptors for high efficiency interception where the oil and effluent discharge is a problem.
- Kirton GH range of effluent for difficult effluents containing emulsified oils and detergents.
- Kirton 'HC' vehicle wash water recycling system.